



TYPICAL PAVEMENT CROSS SECTION
 MAJOR THOROUGHFARES, MINOR THOROUGHFARES,

MINIMUM PAVEMENT SCHEDULE

- Ⓐ 12" COMPACTED AGGREGATE BASE COURSE OR 6" BITUMINOUS CONCRETE BASE COURSE CONFORMING TO CURRENT NCDOT STANDARDS
- Ⓑ 2" BITUMINOUS CONCRETE BINDER CONFORMING TO CURRENT NCDOT STANDARDS, PLACED IMMEDIATELY UPON FINAL PREPARATION OF ABC STONE BASE.
- Ⓒ 2" BITUMINOUS CONCRETE SURFACE COURSE CONFORMING TO CURRENT NCDOT STANDARDS, PLACED IN ONE LIFT WITH TACK COAT BETWEEN BINDER AND SURFACE COURSE.

THE TYPE OF STREET IS TO BE DETERMINED BY THE CITY.

SEE LAND DEVELOPMENT ORDINANCE CHAPTER 4, SECTIONS 4.7 & 4.8 FOR TYPICAL STREET SECTIONS WITH RIGHT-OF-WAY, PAVEMENT WIDTHS, CURB TYPE, DRAINAGE TYPE, SIDEWALK AND TREE REQUIREMENTS, ETC.

NOTE: DESIGN REQUIREMENTS VARY PER ZONING DISTRICT

*PAVEMENT WIDTHS DO NOT INCLUDE CURB & GUTTER

CITY OF SALISBURY, N.C.	STANDARD DETAIL	DATE:	TBD
ROADS PAVEMENT STANDARDS (1)		NOT TO SCALE	
		STANDARD	R-1